## AMCC-25

PERIOD OF 1 YEAR FROM THE DATE OF SHIPMENT.

- NOTE :-
- 1. ALL MEASUREMENTS ARE DONE AT ROOM TEMPERATURE.

TOLERANCES UNLESS OTHERWISE SPEC

- 2. WEIGHT INCLUDES 2% EPOXY WEIGHT.
- 3. CONTINUOUS OPERATING TEMPERATURE: 155°C

## CORE MATERIAL: MEGLAS®ALLOY 2605SA1

# UTHORIZED IN WRITING. ANY PERSON WHO

IFIED	NO.	REVISION	BY	APPR.	DATE	DIMENSIONS	MM
	1.)	CORE LOSS WAS WRITTEN MEASURED @ 0.37T BY MISTAKE,INSTEAD OF 0.037T		SR	04/19/02	SCALE	N.T.S
	2.)	COMPANY NAME WAS HONEYWELL.	SA	RK	02/14/04	PROJECTION	THIRD
	3.)	ADDED NOTE#3 . (AS PER PCN002).	SA	RK	07/26/04		
	4.)	PRODUCT & DRAWING FORMAT REVISED. (AS PER PCN004)	RG	RK	25/09/06	HIT	CACI
						MET	$\Gamma GL_{A}$

## PHYSICAL SPECIFICATIONS

1.) CUSTOMER TO MARK THE DIMENSIONS/CHARACTERISTICS THAT ARE CRITICAL TO FIT/FORM AND

2.) NUMBER OF COMPONENTS TO BE SUBMITTED FOR PILOT PRODUCTION LOT= PIECES. 3.) UNLESS OTHERWISE SPECIFIED, STANDARD PACKAGING USED BY HITACHI METGLAS WILL BE

4.) ALL PRODUCTION RECORDS AND DATA PERTAINING TO THIS PRODUCT WILL BE RETAINED FOR A

(a) mm	$13.0\pm0.8$
(b) mm	15.0+1.0/-0.0
(c) mm	56.0+2.0/-0.0
(d) mm	25.0+0.5/-0.0
(e) mm	41.0+1.0/-0.5
(f) mm	82.0+2.0/-0.0
(Im) cm	19.60
	2.70
(Wa) cm <sup>2</sup>	8.40
(Ap) cm <sup>4</sup>	22.70
g	380 (Nom.)
	(b) mm (c) mm (d) mm (e) mm (f) mm (Im) cm (Ac) cm <sup>2</sup> (Wa) cm <sup>2</sup>

### ELECTRICAL SPECIFICATIONS

Core Loss @ 16kHz, 0.037 T ≤ 1.38W\Kq.

DESCRIPTION

Im = mean magnetic path length

Ac = net cross-sectional area

Wa = core window area

			C - C ORF DESIGN					NO.		NO.		NO.
	SCALE	N.T.S	MATERIA	ıL.	AS NOTED					AMC C - 25		
	PROJECTION	THIRD ANGLE										4
НІТАСН				SR	07/12/01	SR	07/12	/01	RH,	RM,ST	07/1	9/01
$\perp$ METGLA		S	DRAWN	DATE	CHECKED	DAT	E	APP	ROVED	DA	TE	

SHEET DRAWING REV.

#### EG/FM/11/2